



Rivestimento in legno
Covering in wood

TCE/10L



Art Code	Misure esterne mm. External dim. mm.			Misure interne mm. Internal dim. mm.			Dim. porta mm. Door dim. mm.		Numero catenacci Number of bolts	Peso Weight	Litri Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Kg	Lt
TCE/5L	1510	440	345	1300*	335	245	1325	270	4	66	119
TCE/10L	1510	635	385	1300*	530	285	1325	460	4	99	218

* Esclusa l'altezza della cassetta interna

* Excluding the high of security box



Combinazione Elettronica con Display

- Struttura monoblocco in lamiera d'acciaio dello spessore di 2 mm.
- Porta spessore 3 mm.
- Spessore totale del battente 55 mm.
- Serratura controllata da un congegno elettronico dotato di memoria permanente.
- Tastiera a pulsanti in speciale abs, completa di display LCD retroilluminato a 8 posizioni.
- Apertura in caso di emergenza con serratura a chiave (2 chiavi fornite).
- Alimentazione con 4 batterie alcaline da 1,5 V (in dotazione).
- 4 catenacci frontali in acciaio nichelato del Ø di 20 mm.
- Rastrelliera in legno ricoperta in tessuto e tappetino sulla base.
- Tesoretto interno portamunizioni con serratura a cilindro.
- Fori di ancoraggio sulla base e sullo schienale (2+2).

TCE/5L: • con tesoretto - 5 fucili

TCE/10L: • con tesoretto - 10 fucili



Digital Electronic Combination with Display

- One-piece steel construction with a body's thickness of 2 mm.
- Thickness of door 3 mm.
- Total door thickness (with lock-panel): 55 mm.
- Lock controlled by an electronic system with permanent memory.
- 8 position back lighted LCD display.
- Lock for emergency opening (2 keys supplied).
- Power with 4 batteries 1,5 V (included).
- 4 frontal nickel-plated steel bolts Ø 20 mm.
- Equipped with wood supports covered with textile and inside base with carpet.
- Internal security box with cylinder lock.
- Pre-drilled anchor holes on floor and wall mounting (2+2).

TCE/5L: • with sec. box - 5 rifles

TCE/10L: • with sec. box - 10 rifles