



GMK/5



- Frontale e Porta 10 mm
- Corpo 5 mm
- Taglio Laser

- Front and Door 10 mm
- Body 5 mm
- Laser Cut



CERTIFICATA A
NORMA EUROPEA
UNI EN 14450-S2

CERTIFIED TO
EUROPEAN STANDARD
EN 14450-S2



EVO-LOCK



Double-Bitted Key

- Latest generation high security lock, EN 1300 certified, with 8 asymmetrical and independent levers.

It is based upon the use of new antipicking oscillating levers and mentonnet with special profile to oppose exceptional resistance to assaults with the latest sophisticated tamper systems using special picklocks.

- Double-bitted key with special profile, duplicable with the ownership card, to prevent unauthorized key duplication.
- Key-retaining lock in open position.
- Nickel-plated rotating steel bolts \varnothing 22mm.
- Lock mechanism protected by a manganese-steel plate.
- Horizontal and top vertical bolts protected by drill resistant manganese-steel plate 3mm thick, placed askew in order to get the best resistance to drilling.
- Special door battens for exceptional resistance against robbery attempts using a sledge hammer.
- Internally welded by a robot-controlled system.
- Front panel seam-welded to the casing by a robot-controlled system.
- Removable internal shelf.
- Base and back fixing holes.
- Screw anchor fixing bolts provided.
- Oven dried thermo-hardening powder painting.

Art Code	Misure esterne mm.			Misure interne mm.			Dim. porta mm.		Numero catenacci			Peso	Litri
	External dim. mm.			Internal dim. mm.			Door dim. mm.		Number of bolts			Weight	Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Oriz/Horiz	Vert		Kg	Lt
GMK/3	220	350	300	200	340	245	140	250	2	-		25	18
GMK/4	280	400	350	260	390	295	195	300	2	1+1		35,5	31
GMK/5	350	470	350	330	460	295	265	370	3	1+1		47,5	47
GMK/6	430	490	350	410	480	295	345	390	3	2+2		56	60
GMK/7	490	430	400	470	420	345	405	330	3	2+2		61	70